

TESLA-EXT



Description

Applications: The Tesla EXT 1-Watt endpoint is perfect for deep meter pit or vault environments. It is designed for use with the RG3 encoder registers, as well as, most other manufactures' encoder or pulse registers (ABB, Badger, Neptune, Sensus, Muller, Zenner, Master Meter, Honeywell, etc.). The Tesla EXT endpoint provides 2-way wireless connectivity with RG3 Tesla Drive software eliminating the need for physical access to the meter after installation.

Alarms: The Tesla EXT endpoint notifies the utility of Back flow, Tamper, Leak, and Battery Status flags as they occur in the extended RF message.

Time Sync for Water Loss Identification: Every time the Tesla EXT endpoint reads, it syncs time with the reading device. Tesla EXT endpoint time sync is a 2-Way transmission function and can only be accomplished with true 2-way communication. This feature is important because water loss identification through metering requires the comparison of water volumes recorded by customer and mainline meters over a specific period of time to the water volumes discharged from the treatment facilities or the volume passing through system zone meters over this same period of time. Distribution leak detection requires time synchronization to avoid "clock drift", a phenomena where two clocks do not run at the exact speed and after a period of time, "drift apart". By syncing time with the reading device, Tesla EXT endpoint avoids clock drift completely and delivers the most accurate leak detection possible.



Specifications

Humidity	0 to 100% condensing
Temperature	-40° to 185°F (-40° to 85°C)
Status Indicators	Included in the RF message: Totalizer, flow rate, back-flow, leak, battery indicator (including 20% battery life alarm)
Signal Output	1-Watt RF Transmission
Signal Type	Unlicensed Frequency (902 MHz-928 MHz)
Battery	D cell lithium thionyl chloride battery with capacitor, fully potted and fully encapsulated within the Tesla EXT housing
Battery Life	25 Years (calculated)
Warranty	20 Years (Prorated)
Weight	1 lbs
Length	6 -1/4 inches
Width	Cap - 3 -3/8 inches
Diameter	Body - 2.1/16 inches
Width of Cap at Threads	1.98" (2-1/8" pit lid hole required)



2912 South Access Rd.
Longview, TX 75602
PH: 903-753-3456
Fax: 903-753-5678
RG3METER.COM



Tesla EXT- EXTDS12241

Transmission: Tesla EXT endpoint technology starts where the rest of the industry's most advanced solutions top out. All of functions are accomplished through streamlined 2-way communication utilizing the FCC approved unlicensed 902-928 MHz band. To ensure transmission success, Tesla EXT endpoint employs Cyclic Redundancy Checks (CRC), Spread Spectrum Frequency Hopping Modulation, and Channel Coding.

Transmission Power: Tesla EXT endpoint transmits at a full 1-watt. Unlike 1-way bubble up technologies that throw hundreds of thousands of wasted transmissions and large amounts of unnecessary energy into the atmosphere each month, Tesla EXT endpoint's extremely efficient 1 watt power is environmentally friendly. Although Tesla EXT endpoint has 10 times the transmission power of other leading AMR technologies, the total monthly output of electromagnetic radiation is at least 10,000 times less than comparable technologies, or roughly 5% of the amount emitted by the average cell phone each month in the US.

Drive-By (AMR) Read: Tesla EXT transmits its associated meter number, current read, number of digits transmitted, unit of measurement, battery status, leak counter, and back flow, tamper, and leak flags as applicable. Individual meters can be read alone or all meters can be read at once.

Connectors: The Tesla EXT endpoint comes standard with a RG3 connector, rated for use in water depths of up to 30 feet. Nicor and Bare-wire assemblies are also available.

Construction: The Tesla EXT shroud assembly is constructed from engineered polycarbonate and hermetically sealed. The enclosure is UV-resistant, weatherproof, and fully encapsulated to withstand harsh environments and to protect the solid state electronics. The Tesla EXT endpoint is suitable for installation in all environments, including continuously submerged water meter pits. Electronic circuitry is gold plated to provide increased corrosion resistance before it is encapsulated by high quality potting material. Electronics are designed to provide immunity to electrical surges. The power source is an internal lithium battery with capacitor that is also encapsulated in potting for redundant protection against moisture.

Electrical: All mechanical and electronic devices are subject to the effects of their environment. The Tesla EXT endpoint is equipped with an internal watchdog that reboots the electronics if faced with an external interference such as a close proximity lightning strike or other uncontrollable event. Tesla EXT electronic circuitry is designed to provide immunity to electrical surges and transients per IEC801-2, IEC801-4 Severity Level 4.

Data Log / Consumption: Tesla EXT retains 120 days of hourly data. Consumption data can be wirelessly extracted at the meter site.



2912 South Access Rd.
Longview, TX 75602
PH: 903-753-3456
Fax: 903-753-5678
RG3METER.COM

TESLA-EXT



Tesla EXT- EXTDS12241